

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580

Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

Material Safety Data Sheet

Date: January 4, 2010

SECTION I—PRODUCT IDENTIFICATION

NAME: 1-2-3[®] Premix Plus

DOT CLASS: Non-regulated

UN NUMBER: NA

PROPER SHIPPING NAME: NA

HMIS RATING

HEALTH	2
FIRE	0
REACTIVITY	0

SECTION II - INGREDIENTS

ALL COMPONENTS APPEAR ON THE TSCA INVENTORY. COMPONENTS NOT LISTED IS EITHER NON HAZARDOUS OR IN CONCENTRATIONS OF LESS THAN 1%.

Ingredient Name	CAS Number	OSHA PEL	ACGIH TLV/TWA
Alcohols, C10-12, Ethoxylated	66455-15-0	NA	NA
(Poly(oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)-omega-hydroxy, branched)	127087-87-0 26027-38-3 9016-45-9	NA	NA
Alkoxyated Alcohols, C-8-C18	69013-18-9	NA	NA
Iron	7439-89-6	NA	NA
Vitamin B1 (Thiamine)	532-43-4	NA	NA
Vitamin C (Ascorbic Acid)	50-81-7	NA	NA
Vitamin E (a-Tocopherol)	7695-91-2	NA	NA
Water	7732-18-5	NA	NA

SECTION III – PHYSICAL CHARACTERISTICS

Boiling Point	212° F	Appearance and Odor	Pale brown colored liquid. Mild earthy odor.
Specific Gravity	1.14 – 1.16	Melting Point	NA
pH	5.0 - 5.7	Vapor Density	Equivalent to water
Vapor Pressure	Equivalent to water	Solubility	Complete

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580
Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

SECTION IV – FIRE/EXPLOSION

Flash Point:	> 400° F
Flash Point Method Used:	Cleveland Cup
LEL	NA
UEL:	NA

Extinguishing Media: Water spray, carbon dioxide, and dry chemical powder.

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None known.

SECTION V – REACTIVITY DATA

Stable: X **Unstable:**

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition or By Products: Intense heat could cause product to release COx and hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION VI – HEALTH HAZARD DATA

Acute Health Affects

Routes of Entry:	Inhalation: Yes	Absorption: Yes	Ingestion: Yes	Eyes: Yes
-------------------------	------------------------	------------------------	-----------------------	------------------

California Prop 65:

The following detectable components of this product are substances, or belonging to classes of substances, known to the state of California to cause cancer and/or reproductive toxicity.

This product contains residual ethylene oxide (typical) CAS number 75-21-8

Eyes: This product will cause eye irritation.

Skin Contact: Prolonged contact may cause irritation, contact dermatitis and drying of the skin.

**Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042**

Telephone number: 800-233-0628 Fax: 800-806-8580

Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

Inhalation: Inhaling mist from this product could cause irritation to the lungs and mucus membranes.

Ingestion: Ingestion may result in abdominal pain, nausea and vomiting.

Conditions to Avoid: Avoid containers and piping made from aluminum, copper alloys and/or galvanized metal.

Signs and Symptoms of Over Exposure: None Known

Aggravated Medical Conditions: None known, however persons with respiratory problems should avoid breathing any mist from this product.

Emergency First Aid Procedures

Eye Contact: Rinse eyes with water for fifteen minutes, if irritation persists, see a physician.

Inhalation: Move person to fresh air and avoid breathing dust from product. If breathing problems develop, seek the care of a physician.

Skin Contact: Wash the product off the skin with soap and water; if irritation develops seek the care of a physician.

Ingestion: Do not induce vomiting, give victim water to dilute and seek immediate medical attention.

SECTION VII – SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled or leaked:

Waste Disposal Method: Contain and collect material, place in proper container for reuse or disposal. Dispose of materials in accordance with all federal, state and local laws.

Precautions To Be Taken In Handling and Storage: Store in a location away from children, food items and potable water.

Store in an area out of the direct sunlight, store between 40° F and 90° F, product will freeze below 32° F, keep container closed when not in use.

Always wash hands with soap and water before handling food or smoking.

Use good chemical hygiene practices when working with any chemical.

Other Precautions: None

SECTION VIII – CONTROL MEASURES (PPE)

Respiratory Protection: None required for normal use.

Protective Gloves: Wear rubber chemical resistant gloves to prevent skin contact.

Eye Protection: Safety glasses with side shields or splash goggles/splash shield are recommended.

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580

Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

Other Protective Clothing: A rubber apron is recommended to prevent skin contact if product is used in manner that creates splashing.

Ventilation: Local exhaust should be sufficient. If used in a manner that creates a mist, mechanical ventilation may be necessary.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal, state and local laws.