

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580
Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

Material Safety Data Sheet

Date: January 4, 2010

SECTION I—PRODUCT IDENTIFICATION

NAME: FE 8%®

DOT CLASS: Non-regulated
UN NUMBER: NA
PROPER SHIPPING NAME: NA

HMIS RATING

HEALTH	1
FIRE	0
REACTIVITY	0

SECTION II - INGREDIENTS

ALL COMPONENTS APPEAR ON THE TSCA INVENTORY. COMPONENTS NOT LISTED IS EITHER NON HAZARDOUS OR IN CONCENTRATIONS OF LESS THAN 1%.

Ingredient Name	CAS Number	NIOSH TWA	ACGIH Ceiling
Water	7732-18-5	NA	NA
Potassium Hydroxide	1310-58-3	2mg/m3	2mg/m3

SECTION III – PHYSICAL CHARACTERISTICS

Boiling Point	212 F	Appearance and Odor	Dark green liquid, slight odor.
Specific Gravity	1.30 – 1.35	Melting Point	NA
pH	6.2 – 7.0	Vapor Density	As water
Vapor Pressure	NA	Solubility	100 %

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580
Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

SECTION IV – FIRE/EXPLOSION

Flash Point:	NA
Flash Point Method Used:	NA
LEL	NA
UEL:	NA

Extinguishing Media: Water spray, carbon dioxide, and dry chemical powder.

Special Fire Fighting Procedures: Use water to keep containers cool.

Unusual Fire and Explosion Hazards: Toxic / corrosive fumes may be released if exposed to high temperatures.

SECTION V – REACTIVITY DATA

Stable: X **Unstable:**

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition or By Products: Not known

Hazardous Polymerization: Will not occur.

SECTION VI – HEALTH HAZARD DATA

Acute Health Affects

Routes of Entry:	Inhalation: Yes	Absorption: No	Ingestion: Yes	Eyes: Yes
-------------------------	------------------------	-----------------------	-----------------------	------------------

Eyes: This product will cause eye irritation upon contact.

Skin Contact: Prolonged contact may cause irritation, contact dermatitis and drying of the skin.

Inhalation: Inhaling mist from this product could cause irritation to the lungs and mucus membranes.

Ingestion: Ingestion may result in abdominal pain, nausea and vomiting.

Conditions to Avoid: Avoid containers and piping made from aluminum, copper alloys and/or galvanized metal.

Signs and Symptoms of Over Exposure: None Known

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580
Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

Aggravated Medical Conditions: None known, however persons with respiratory problems should avoid breathing any mist from this product.

Emergency First Aid Procedures

Eye Contact: Rinse eyes with water for fifteen minutes, if irritation persists, see a physician.

Inhalation: Move person to fresh air and avoid breathing mist from product. If breathing problems develop, seek the care of a physician.

Skin Contact: Wash the product off the skin with soap and water; if irritation develops seek the care of a physician.

Ingestion: Watch victim for any signs of illness, give water to dilute and seek medical attention immediately.

SECTION VII – SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled or leaked:

Waste Disposal Method: Contain and collect material, place in proper container for reuse or disposal. Dispose of materials in accordance with all federal, state and local laws.

Precautions To Be Taken In Handling and Storage: Store in a location away from children, food items and potable water.

Store in an area out of the direct sunlight, avoid storing at high temperatures.

Always wash hands with soap and water before handling food or smoking.

Use good chemical hygiene practices when working with any chemical.

Other Precautions: None

SECTION VIII – CONTROL MEASURES (PPE)

Respiratory Protection: None required for normal use.

Protective Gloves: Recommended. Rubber gloves are suitable for preventing prolonged contact with the skin.

Eye Protection: Safety glasses with side shields or splash goggles are recommended.

Other Protective Clothing: None required, however, avoid prolonged contact with the skin from soiled clothing.

Ventilation: Local exhaust should be sufficient. If used in a manner that creates a mist, mechanical ventilation may be necessary.

Lebanon Seaboard Corporation
1600 East Cumberland Street
Lebanon, PA 17042

Telephone number: 800-233-0628 Fax: 800-806-8580

Emergency Contact: 888-208-1368 PROSAR CHEMTREC: 1-800-424-9300

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal, state and local laws.